

BLANCO INMOTION product overview

Basket dispenser for installation

- **Material CNS 18/10** with micro-polished surface,
- **Spring tension** can be adapted to the weight of the respective porcelain and/or system parts,
- The basket dispenser is open to allow **installation from below**.

Also for CEBH 50/50:

- **Interior unit temperature** adjustable from +30°C to +110°C,
- **With polycarbonate hooded cover** (with heated use of the units, operation should usually occur with the hooded cover to prevent unnecessary heat loss),
- **Suitable for optimization systems,**

- Pursuant to **DIN 18665, Part 6**
- **VDE and GS certified, CE compliant,**
- **Mains voltage 220-240 V, 50 Hz.**



Model	CEB 50/50	CEBH 50/50
	unheated	heatable
Dimensions LxWxH (in mm)	600 x 545 x 765 to 865 mm	700 x 691 x 785 mm
Interior dims (in mm)	520 x 520 mm	520 x 520 mm
Weight (in kg)	19.0 kg	64.5 kg
Wattage	—	1.8 kW
Capacity	6 baskets (each 115 mm high) or 10 baskets (each 75 mm high)	6 baskets (each 115 mm high) or 10 baskets (each 75 mm high)
Stack height	w/o hooded cover: 540 mm w/ hooded cover: 680 mm (hooded cover as accessory)	w/o hooded cover: 540 mm w/ hooded cover: 680 mm (including hooded cover)
Special features	—	Incl. polycarbonate hooded cover (557 x 557 mm)
Accessories/ Options	Hooded cover (polycarbonate) Steel wire baskets, plastic-coated, 500 x 500 x 75 mm or 500 x 500 x 115 mm Stainless steel baskets, CNS 18/10, 500 x 500 x 75 mm or 500 x 500 x 115 mm All-round flange for installation from above (Order No. 590 103)	Steel wire baskets, plastic-coated, 500 x 500 x 75 mm or 500 x 500 x 115 mm Stainless steel baskets, CNS 18/10, 500 x 500 x 75 mm or 500 x 500 x 115 mm
Order No.	590 025	572 206

We will be happy to provide you with additional information on the BLANCO INMOTION and on the entire BLANCO product line on request.