


# BLANCO INMOTION product overview

## Plate dispenser, heatable

- **Material CNS 18/10** with micro-polished surface,
- **Interior unit temperature** adjustable from +30°C to +110°C (2 SHVS 21-26: up to +130°C),
- **Powerful heating element** made of CNS 18/10,
- **With polycarbonate hooded cover** (with heated use of the units, operation should usually occur with the hooded cover to prevent unnecessary heat loss),
- **Synthetic guide rods** prevent porcelain from being worn,
- **Spring tension** can be adjusted to the weight of the respective plates,
- **CNS safety push handle** with side corner guard elements also serves to protect the switch elements,
- **Protected against splashed and sprayed water** (IPX 5),
- **Suitable for optimization systems**,
- Pursuant to **DIN 18665, Part 6**
- **Synthetic castors**, 4 steering castors, 2 of which have brakes, dia. 125 mm, corrosion-resistant pursuant to DIN 18867, Part 8,
- **Solid corner guards** made of plastic (polyamide) protect against damage,
- **VDE and GS certified, CE compliant**,
- **Operating panel** with on/off switch, pilot lamp, helix cord connection with dummy plug socket, temperature control on the short side below the push handle,
- **Mains voltage of SHV and SHVS:** 220-240 V, 50 Hz, **SHE:** 220-240 V, 50-60 Hz.



Model	1 SHE 21-26	1 SHE 26-31	2 SHE 21-26	2 SHE 26-31
	heatable	heatable	heatable	heatable
<b>Dimensions LxWxH (in mm)</b>	653 x 513 x 931 mm Operating height: 900 mm	653 x 513 x 931 mm Operating height: 900 mm	898 x 513 x 931 mm Operating height: 900 mm	1,018 x 513 x 931 mm Operating height: 900 mm
<b>Interior dims (in mm)</b>	dia. 210-260 mm	dia. 260-310 mm	dia. 210-260 mm	dia. 260-310 mm
<b>Weight (in kg)</b>	34.5 kg	35.0 kg	45.0 kg	49.5 kg
<b>Wattage</b>	0.9 kW	0.9 kW	1.8 kW	1.8 kW
<b>Capacity</b>	1 tube, approx. 60 plates total capacity	1 tube, approx. 60 plates total capacity	2 tubes, approx. 120 plates total capacity	2 tubes, approx. 120 plates total capacity
<b>Stack height</b>	w/o hooded cover: 620 mm w/ hooded cover: 670 mm (including hooded cover)	w/o hooded cover: 620 mm w/ hooded cover: 670 mm (including hooded cover)	w/o hooded cover: 620 mm w/ hooded cover: 670 mm (including hooded cover)	w/o hooded cover: 620 mm w/ hooded cover: 670 mm (including hooded cover)
<b>Special features</b>	Incl. polycarbonate hooded cover	Incl. polycarbonate hooded cover	Incl. polycarbonate hooded cover	Incl. polycarbonate hooded cover
<b>Accessories/Options</b>	Lid lock on the cover Decorative model For other castor designs, see Page 31	Lid lock on the cover Decorative model For other castor designs, see Page 31	Lid lock on the cover Decorative model For other castor designs, see Page 31	Lid lock on the cover Decorative model For other castor designs, see Page 31
<b>Order No.</b>	572 162	572 163	572 164	572 165



Model	2 SHV 21-26	2 SHV 26-31	2 SHVS 21-26
	heatable (convection)	heatable (convection)	heatable (convection)
<b>Dimensions LxWxH (in mm)</b>	958 x 513 x 931 mm Operating height: 900 mm	1,018 x 513 x 931 mm Operating height: 900 mm	1,018 x 513 x 931 mm Operating height: 900 mm
<b>Interior dims (in mm)</b>	dia. 210-260 mm	dia. 260-310 mm	dia. 210-260 mm
<b>Weight (in kg)</b>	48.0 kg	51.0 kg	59.0 kg
<b>Wattage</b>	1.8 kW	1.8 kW	3.6 kW
<b>Capacity</b>	2 tubes, approx. 120 plates total capacity	2 tubes, approx. 120 plates total capacity	2 tubes, approx. total ca- pacity: 76 heat-retaining plates
<b>Stack height</b>	w/o hooded cover: 620 mm w/ hooded cover: 670 mm (including hooded cover)	w/o hooded cover: 620 mm w/ hooded cover: 670 mm (including hooded cover)	Stack height: 620 mm CNS hinged lids permanently mounted to unit
<b>Special features</b>	Incl. polycarbonate hooded cover  Equipped with convection-blower heating	Incl. polycarbonate hooded cover  Equipped with convection-blower heating	Especially for wax-filled heat-retaining plates made of CNS  Equipped with convection-blower heating
<b>Accessories/ Options</b>	Lid lock on the cover Decorative model For other castor designs, see Page 31	Lid lock on the cover Decorative model For other castor designs, see Page 31	Decorative model For other castor designs, see Page 31
<b>Order No.</b>	572 166	572 167	572 168

We will be happy to provide you with additional information on the BLANCO INMOTION and on the entire BLANCO product line on request.

## BLANCO INMOTION product overview

Plate dispenser, unheated

Plate dispenser with cooling slits

- **Material CNS 18/10** with micro-polished surface,
- **Spring tension** can be adjusted to the weight of the respective plates,
- **Synthetic guide rods** prevent porcelain from being worn,
- **CNS safety push handle** with side corner guard elements,

- **Synthetic castors**, 4 steering castors, 2 of which have brakes, dia. 125 mm, corrosion-resistant pursuant to DIN 18867, Part 8,
- **Solid corner guards** made of plastic (polyamide) protect against damage.

Also for 2 SEK 21-26 and 2 SEK 26-31:

- **Unit body with cooling slits** to cool dishes in refrigerated rooms.



Model	2 SE 21-26	2 SE 26-31	2 SEK 21-26 (without plates)	2 SEK 26-31
	unheated	unheated	with cooling slits	with cooling slits
<b>Dimensions LxWxH (in mm)</b>	788 x 513 x 931 mm Operating height: 900 mm	818 x 513 x 931 mm Operating height: 900 mm	788 x 513 x 931 mm Operating height: 900 mm	869 x 513 x 931 mm Operating height: 900 mm
<b>Interior dims (in mm)</b>	dia. 210-260 mm	dia. 260-310 mm	dia. 210-260 mm	dia. 260-310 mm
<b>Weight (in kg)</b>	26.5 kg	28.0 kg	26.0 kg	27.0 kg
<b>Capacity</b>	2 tubes, approx. 120 plates total capacity	2 tubes, approx. 120 plates total capacity	2 tubes, approx. 120 plates total capacity	2 tubes, approx. 120 plates total capacity
<b>Stack height</b>	w/o hooded cover: 620 mm w/ hooded cover: 670 mm (hooded cover as accessory)	w/o hooded cover: 620 mm w/ hooded cover: 670 mm (hooded cover as accessory)	w/o hooded cover: 620 mm w/ hooded cover: 670 mm (hooded cover as accessory)	w/o hooded cover: 620 mm w/ hooded cover: 670 mm (hooded cover as accessory)
<b>Special features</b>	—	—	Unit body with cooling slits	Unit body with cooling slits
<b>Accessories/Options</b>	Polycarbonate hooded cover Decorative model Lid lock on the cover For other castor designs, see Page 31	Polycarbonate hooded cover Decorative model Lid lock on the cover For other castor designs, see Page 31	Polycarbonate hooded cover Lid lock on the cover For other castor designs, see Page 31	Polycarbonate hooded cover Lid lock on the cover For other castor designs, see Page 31
<b>Order No.</b>	572 173	572 174	572 175	572 176