


## BLANCO INMOTION product overview

Basket dispenser, heatable

Basket dispenser, cooled (convection)

- **Material CNS 18/10** with micro-polished surface,
- **Interior unit temperature can be regulated** from +30°C to +110°C (CE-UK 53/53: +2°C to +15°C, with ambient temperature of +32°C),
- **With polycarbonate hooded cover** (with heated or cooled use of the units, operation should usually occur with the hooded cover to prevent unnecessary heat/cool air loss),
- **Spring tension** can be adapted to the weight of the respective porcelain and/or system parts,
- **CNS safety push handle** with side corner guard elements also serves to protect the switch elements,
- **CHV 53/53 and CHV 66/54: Protected against splashed and sprayed water** (IPX 5), **CE-UK 53/53: Protected against splashed water** (IPX 4),
- **Suitable for optimization systems**,
- Pursuant to **DIN 18665, Part 6**
- **Synthetic castors**, 4 steering castors, 2 of which have brakes (CE-UK 53/53: 2 fixed and 2 steering castors with brakes), dia. 125 mm, corrosion-resistant pursuant to DIN 18867, Part 8,
- **Solid corner guards** made of plastic (polyamide) protect against damage,
- **VDE certified and GS mark** (not CE-UK 53/53), **CE conformity**,
- **Operating panel** with on/off switch, pilot lamp, CHV 53/53 and CHV 66/54: Helix cord connection with dummy plug socket, temperature control below the push handle, CE-UK 53/53: digital temperature control below the push handle, helix cord connection and dummy plug socket on long side of unit,
- **Mains voltage** 220-240 V, 50 Hz.



Model	CHV 53/53	CHV 66/54	CE-UK 53/53
	heatable (convection)	heatable (convection)	cooled (convection)
<b>Dimensions LxWxH (in mm)</b>	898 x 714 x 931 mm Operating height: 900 mm	1,038 x 714 x 931 mm Operating height: 900 mm	1,313 x 790 x 1,065 mm Operating height: 900 mm
<b>Interior dims (in mm)</b>	535 x 535 mm	660 x 540 mm	535 x 535 mm
<b>Weight (in kg)</b>	70.0 kg	72.0 kg	117.0 kg
<b>Wattage</b>	1.8 kW	1.8 kW	0.4 kW
<b>Capacity</b>	6 baskets of height 115 mm or 9 baskets of height 75 mm	6 baskets of height 115 mm or 9 baskets of height 75 mm	5 baskets of height 115 mm or 8 baskets of height 75 mm
<b>Stack height</b>	w/o hooded cover: 540 mm w/ hooded cover: 680 mm (including hooded cover)	w/o hooded cover: 540 mm w/ hooded cover: 680 mm (including hooded cover)	without hooded cover: 540 mm with hooded cover: 680 mm (including hooded cover)
<b>Special features</b>	Equipped with convection-blower heating Incl. polycarbonate hooded cover (557 x 557 mm)	Equipped with convection-blower heating Incl. polycarbonate hooded cover (697 x 697 mm)	Convection cooling, cooling capacity: 0.37 kW at $t_0 = -10^\circ\text{C}$ (evaporation temp.) and $t_a = +32^\circ\text{C}$ (ambient temp.), coolant CFC-free (R 134a) Incl. polycarbonate hooded cover (557 x 557 mm)
<b>Accessories/options</b>	Steel wire baskets, plastic-coated, 500 x 500 x 75 mm or 500 x 500 x 115 mm, 525 x 525 x 75 mm or 525 x 525 x 115 mm Stainless steel baskets, CNS 18/10, 500 x 500 x 75 mm or 500 x 500 x 115 mm, 525 x 525 x 75 mm or 525 x 525 x 115 mm Decorative model For other castor designs, see Page 31	Steel wire baskets, plastic-coated, 650 x 530 x 75 mm or 650 x 530 x 115 mm Stainless steel baskets, CNS 18/10, 650 x 530 x 75 mm or 650 x 530 x 115 mm Decorative model For other castor designs, see Page 31	Steel wire baskets, plastic-coated, 500 x 500 x 75 mm, 500 x 500 x 115 mm, 525 x 525 x 75 mm, 525 x 525 x 115 mm Stainless steel baskets, CNS 18/10, 500 x 500 x 75 mm, 500 x 500 x 115 mm, 525 x 525 x 75 mm, 525 x 525 x 115 mm 12 guide rods for use of the unit as a universal dispenser (Order No. 572 454) All-round bumper rail made of plastic (polyamide) For other castor designs, see Page 31
<b>Order No.</b>	572 185	572 186	572 431

We will be happy to provide you with additional information on the BLANCO INMOTION and on the entire BLANCO product line on request.

